# Nature Shield (600, 350 & 100 VOC)



Section 1Product DescriptionProduct Name:Nature Shield 600, 350, & 100Recommended Use:Water Repellent Concrete SealerSupplier:Duracorp, 2664 Vista Pacific, Oceanside, CA 92056 (760-758-7240)Emergency Phone:CHEMTREC 1-800-424-9300

#### Section 2

## Hazard identification

Nature Shield VOC 600:

Category 2 Flammable Liquid Category 4 Acute Inhalation Toxicity Category 5 Acute Dermal Toxicity Category 2A Eye Irritation Category 2 Carcinogen Category 3 Specific Target Organ Acute Toxicity (respiratory system, central nervous system) Category 2 Specific Target Organ Chronic Toxicity (liver, kidney, central nervous system) Category 1B Germ Cell Mutagenicity Category 2 Skin Irritant Category 2 Acute Aquatic Toxicity



Signal Word:

Danger

Hazard Statements:

- H225 Highly flammable liquid and vapor
- H313 May be harmful in contact with skin
- H315 Causes skin irritation
- H319 Causes serious eye irritation
- H332 Harmful if inhaled
- H335 May cause respiratory irritation
- H336 May cause drowsiness or dizziness
- H340 May cause genetic defects
- H351 Suspected of causing cancer
- H361 Suspected of damaging fertility or the unborn child
- H373 May cause damage to organs through prolonged or repeated exposure
- H401 Toxic to aquatic life

Precautionary statements:

#### **Prevention:**

P210 Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking P233 Keep container tightly closed

P260 Do not breathe mist/vapors/spray

P264 Wash skin thoroughly after handling

P271 Use only outdoors or in a well-ventilated area

P281 Use personal protective equipment as required

#### **Response:**

P301+P312+P331 IF SWALLOWED: Do NOT induce vomiting. Immediately call a poison center or doctor/physician if you feel unwell.

P303+P361+P353 IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower



P304+P340+P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician if you feel unwell.
P305+p351+p338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333+P313 If skin irritation or rash occurs, get medical advice/attention
P370+P378 In case of fire: Use dry sand, dry chemical, or alcohol-resistant foam for extinction
Storage:
P403+P233+P235 Store in a well-ventilated place. Keep container tightly closed. Keep cool.
Disposal:
P501 Dispose of contents/container in accordance with local/federal regulations.

#### Nature Shield VOC 100:

Category 2 Flammable Liquid Category 2A Eye Irritation Category 3 Specific Target Organ Acute Toxicity (respiratory system) Category 2 Skin Irritant Category 1 Skin Sensitization Category 3 Acute Aquatic Toxicity



Signal Word:

Danger

Hazard Statements:

H225 Highly flammable liquid and vapor

H315 Causes skin irritation

H317 May cause an allergic skin reaction

- H319 Causes serious eye irritation
- H335 May cause respiratory irritation
- H402 Harmful to aquatic life

#### Precautionary statements:

#### **Prevention:**

P210 Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking

P233 Keep container tightly closed

P260 Do not breathe mist/vapors/spray

P264 Wash skin thoroughly after handling

P271 Use only outdoors or in a well-ventilated area

P281 Use personal protective equipment as required



#### **Response:**

P301+P312+P331 IF SWALLOWED: Do NOT induce vomiting. Immediately call a poison center or doctor/physician if you feel unwell.

P303+P361+P353 IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower

P304+P340+P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician if you feel unwell.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs, get medical advice/attention

P370+P378 In case of fire: Use dry sand, dry chemical, or alcohol-resistant foam for extinction Storage:

P403+P233+P235 Store in a well-ventilated place. Keep container tightly closed. Keep cool. **Disposal:** 

P501 Dispose of contents/container in accordance with local/federal regulations.

#### Section 3 **Composition/Information on Ingredients**

Nature Shield 600 VOC:	CAS #	OSHA PEL(TWA)	ACGIH(TLV-TW	A) Conc.(wt. %)
Acrylic polymer Dimethylketone t-Butyl Acetate Light Solvent Naptha Trimethylbenzene 1,2,4-Trimethylbenzene Cumene Mixed Xylene Isomers Cymenes Alkylsilane Alkylsiloxane	Proprietary 67-64-1 540-88-5 64742-95-6 25551-13-7 95-63-6 98-82-8 1330-20-7 25155-15-1 Proprietary Proprietary	None established 1000 ppm 200 ppm None established 25 ppm 25 ppm(1989 std.) 50 ppm 100 ppm None established None established None established	None established 500 ppm 200 ppm None established 25 ppm 50 ppm 100 ppm None established None established None established	10.0 - 20.0 20.0 - 30.0 15.0 - 30.0 14.0 - 17.0 5.0 - 12.0 1.0 - 2.8 0.0 - 1.4 0.2 - 0.4 1.0 - 10.0 1.0 - 10.0
Nature Shield 100 VOC:	CAS #	OSHA PEL(TWA)	ACGIH(TLV-TWA)	Conc.(wt. %)
Acrylic polymer Dimethylketone p-Chlorobenzotriflouride Alkylsilane Alkylsiloxane	Proprietary 67-64-1 98-56-6 Proprietary Proprietary	None established 1000 ppm None established None established None established	None established 500 ppm None established None established None established	$10.0 - 20.0 \\ 30.0 - 40.0 \\ 30.0 - 50.0 \\ 1.0 - 10.0 \\ 1.0 - 10.0$

#### Section 4 **First Aid Measures**

#### **Emergency First Aid Procedures**

Skin: Clean material from skin with acetone, then wash with soap and water followed by moisturizer. If irritation persists, contact a physician.

Eyes: Flush with a gentle but large stream of clean water for 15 minutes, lifting the lower and upper eyelids occasionally. Remove contact lenses if able. Call a physician if irritation persists.

Inhalation: Move to fresh air and provide oxygen if breathing is difficult. Seek medical attention.

Ingestion: DO NOT INDUCE VOMITING. Give large quantities of water. Do not give milk or alcoholic beverages. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into the lungs. Get medical attention immediately.

#### Section 5 **Firefighting Procedures**

Suitable Extinguishing Media: Dry chemical, CO2, alcohol-resistant foam Unsuitable Extinguishing Media: High-volume water jet Flash Point (TCC): 0° F



#### Flammable Limits (% volume in air for solvents): LEL=0.9 UEL=12.8

**Special Fire Fighting Procedures:** Evacuate area and fight fire from a distance. Firefighters wear NIOSH approved self-contained breathing apparatus. Cool containers exposed to fire with water. Vapors are heavier than air and may travel along the ground to distant ignition sources. Do not allow runoff from firefighting to enter drains or water courses.

#### Section 6 Spill or Leak Procedures

**Steps to Take if Material is Released or Spilled:** No health affects expected from the clean-up of the material if contact can be avoided. Follow the protection information found in Section 8 of this SDS. Ventilate the contaminated area. Prevent the spread of spilled material by using a suitable absorbent material or sand dam.

## Section 7 Handling and Storage

Normal Handling: Always use good industrial hygiene practices and safety guidelines.

from open flame, sparks, or other sources of heat and ignition.

Storage: Store material in its original container. Keep containers tightly closed when not in use. Keep material away

Waste Disposal Method: Liquid material is an ignitable waste (D001). Dispose of material in accordance with federal, state, and local guidelines.

**Special Precautions:** Use proper bonding/grounding techniques to avoid static buildup/discharge, which can ignite vapors. Empty containers may contain explosive levels of vapor. Do not cut, drill, or weld on or near the containers.

## Section 8 Protection Information

**Respiratory Protection:** Use NIOSH-approved organic vapor respirator when exposure levels can't be kept below limits.

Ventilation: Provide adequate mechanical ventilation to keep exposure levels below TLV's.

Protective Gloves: Wear impervious chemical gloves.

Eye Protection: Wear chemical safety glasses.

Other Protective Clothing or Equipment: As needed to prevent repeated/prolonged contact.

**Work/Hygienic Practices:** Use only in adequately-ventilated area unless recommended respiratory protection is used. Wash thoroughly with soap and water after handling and before eating, smoking, or using washroom. If clothes become contaminated, change to clean clothing and wash contaminated clothes before re-use.

## Section 9 Physical Data

Appearance: Clear to slightly hazy liquid Odor: Ketone Odor Threshold: 306 ppm pH: None Freezing/Melting Point: <-70° F Boiling Point: >133° F Flash Point: 0° F Evaporation Rate: No data available Flammability (solid, gas): No data available Lower/Upper Flammability: 0.9 – 12.8 Vapor Pressure: 31 mm Hg at 20° C Vapor Density: No data available Density: 0.87 g/cc (SB 600); 0.94 (SB 350); 1.01 (SB 100) Solubility (w/w in water): 26% (SB 600 & SB 350); 39% (SB 100) Partition Coefficient: No data available Auto-ignition Temperature: No data available Decomposition temperature: No data available Viscosity: 12 - 18 centipoise

#### Section 10 Reactivity Data

Reactivity:StableConditions to avoid:Prevent vapor accumulation. Avoid heat and flames.Incompatibility (Materials to Avoid):Strong oxidizers, acids, alkalies, nitrates.Hazardous Decomposition (Byproducts):Carbon monoxide, carbon dioxide, isobutylene, and acetic acid.Hazardous Polymerization:Should not occur.

Section 11 Toxicity Data Routes of Exposure: Inhalation, Ingestion, eyes, and Skin. Acute Toxicity Lethal Doses (ATE):

#### Nature Shield 600 VOC:

LC50 (inhl) 12.01 mg/l LD50 (oral) 6061 mg/kg LD50 (skin) 4950 mg/kg

#### Nature Shield 100 VOC:

LC50 (inhl) 10000 mg/l LD50 (oral) 7752 mg/kg LD50 (skin) 5650 mg/kg

#### Health Hazards:

Acute: May cause eye, skin, gastrointestinal, and lung irritation. May cause central nervous system depression.

Chronic: Prolonged and repeated exposures to high concentrations may cause liver and kidney damage.

**Skin Contact:** May cause irritation and redness. Prolonged or repeated exposure can cause defatting and drying of the skin which may result in a burning sensation and a dried, cracked appearance.

Eye Contact: Causes redness, tearing, irritation of the eyes. Direct contact may will cause moderate eye irritation.

Inhalation: May cause headache, nausea, dizziness, and loss of coordination. Continued inhalation may result in unconsciousnes.

**Ingestion:** May be harmful if swallowed. Aspiration of the material into the lungs can cause chemical pneumonitis, which can be fatal.

Carcinogen: No components of this product are known carcinogens.

Aggravation of Pre-existing Conditions: Persons with pre-existing skin, eye, or lung disorders may be more susceptible to the effects of the substance.

## Section 12 Ecological Data

Acute Toxicity to Fish (calculated): LL50 (96 hr) 30.4 mg/L (VOC600);22.0 mg/L (VOC100)

Acute Toxicity to Aquatic Invertebrates (calculated): EL50 (48 hr) 12.6 mg/L (VOC600) ;24.0 mg/l (VOC100)

Toxicity to Aquatic Plants (calculated): EL50 algae 6.0 mg/L (VOC600);850.0 mg/L (VOC100)

Toxicity to Microorganisms: High concentrations may be harmful to sewage treatment plant microbes.

Chronic Toxicity to Fish: No data available

Chronic Toxicity to Aquatic Invertebrates: No data available

Persistence and Degradability: Expected to degrade readily and rapidly in the presence of oxygen

**Bioaccumulation Potential:** This material is not expected to bioaccumulate.

Mobility in the Soil: Expected to move slowly in soil and water.

Other Adverse Effects: No data available.

#### Section 13 Disposal Information

**Waste Disposal Method:** Liquid material is an ignitable waste (D001). Dispose of material in accordance with all Federal, State, and Local regulations.

#### Section 14 Transport Information

For all modes: Proper Shipping Name: PAINT Hazard Class: 3 UN: UN1263 Packing Group: PGII Marine Pollutant: No

## Section 15 Regulatory Information

SARA 311/312: Yes. (VOC600 = Fire, Acute, Chronic; VOC100 = Fire, Acute).

**OSHA:** This material is hazardous by definition of Hazardous Communications Standard (29 CFR 1910.1200). **TSCA:** Components of this material are either listed or are exempt from the EPA TSCA Inventory of Chemical Substances.

proline

# proline

Massachusetts Right To Know:			
Nature Shield VOC600:	25551-13-7 95-63-6 1330-20-7	Benzene, trimethyl 1,2,4-Trimethylbenzene Mixed xylenes	14.0 – 17.0 5.0 – 12.0 0.0 – 1.4
Nature Shield SB 100:	This product contains no chemicals listed.		
Pennsylvania Right To Know:			
Nature Shield SB 600:	64742-95-6 25551-13-7 95-63-6 1330-20-7	Light Solvent Naphtha Benzene, trimethyl 1,2,4-Trimethylbenzene Mixed xylenes	15.0 - 30.0 14.0 - 17.0 5.0 - 12.0 0.0 - 1.4
Nature Shield SB 100:	This product contains no chemicals listed.		
New Jersey Right To Know:			
Nature Shield SB 600:	64742-95-6	Light Solvent Naphtha	15.0 - 30.0
	25551-13-7 95-63-6 1330-20-7	Benzene, trimethyl 1,2,4-Trimethylbenzene Mixed xylenes	14.0 – 17.0 5.0 – 12.0 0.0 – 1.4
Nature Shield SB 100:	This product contains no chemicals listed.		

#### Section 16 **Additional Information**

The regulatory information provided is not intended to be comprehensive. Other Federal, State and Local regulations may apply to this material.

#### **CALIFORNIA PROPOSITION 65**

WARNING: This product can expose you to Cumene and Benzene which is known to the State of California to cause cancer, birth defects, and reproductive harm. For more information, go to www.P65Warnings.ca.gov.

## California Proposition 65 - CRT: Listed Date/Carcinogenic substance

Cumene (CAS 98-82-8) Benzene (CAS 71-43-2) Listed: April 2, 2010 Listed: February 27, 1987

SDS Revised Date: September 2018

DISCLAIMER: Although the information and recommendations set forth herein are presented in good faith and believed to be correct as of the date hereof, manufacturer makes no representations as to the completeness or accuracy thereof.